


FD30 Pre-primed F/door NMA (metric)

Internal Door

Engineered Construction



426 / 526 / 626 / 726 / 826 / 926 / 1026 / 1126 / 970



Door Sizes

Product	Thickness mm	Width mm	Length mm	Width inch	Length inch
J470	44	426	2040	17	80
J471	44	526	2040	21	80
J472	44	626	2040	25	80
J473	44	726	2040	28	80
J474	44	826	2040	32	80
J475	44	926	2040	36	80
J476	44	1026	2040	40	80
J469	44	1126	2040	44	80
J477	44	970	2040	38	80

Material Specification

Construction	Stile and Rail Fire-Rated Door Leaf
Stiles and Rails	39.2mm x (38-19)mm Engineered Pine (2 Vertical Stiles + 2 Rails)
Face/Skin	8mm Primed MDF
Core	Low-density Particleboard Fire Core
Glazing Type (if applicable)	-
Edges	Finger-Jointed Softwood
Finishing	Pre-Painted / Primed (Ready for final paint)
Glue (Face)	Glued to the core stiles and rails with UF glue
Fire Rating	FD30 (30-Minute Fire Resistance)
Fire Test & Certification	European Standard EN 1634-1 & British Standard CF 292 Warrington.
Acoustic Performance	Rw ≈ 32 dB (tested to UNE ISO 140-3:1995)