

Data Sheet

FD60 Pre-primed F/Door NMA (metric)

Internal Door

Engineered Construction



Door Sizes

Product	Thickness mm	Width mm	Length mm	Width inch	Length inch
J484	55	426	2040	17	80
J478	55	526	2040	21	80
J479	55	626	2040	25	80
J480	55	726	2040	28	80
J481	55	826	2040	32	80
J482	55	926	2040	36	80
J483	55	1026	2040	40	80

Material Specification

Construction	Stile and Rail Fire-Rated Door Leaf
Stiles and Rails	39.2mm x (38-19)mm Engineered Pine (2 Vertical Stiles + 2 Rails)
Face/Skin	8mm Primed MDF
Core	Low-density Particleboard Fire Core
Glazing Type (if applicable)	-
Edges	Finger-Jointed Softwood
Finishing	Pre-Painted / Primed (Ready for final paint)
Glue (Face)	Glued to the core stiles and rails with UF glue
Fire Rating	FD60 (60-Minute Fire Resistance)
Fire Test & Certification	European Standard EN 1634-1 & British Standard CF 292 Warrington.
Acoustic Performance	Rw ≈ 36 dB (tested to UNE ISO 140-3:1995)

426 / 526 / 626 / 726 / 826 / 926 / 1026

2040