



CALM

LITE COLLECTION

Hakwood

PRODUCT INFORMATION				
	Species	European Oak		
	Surface texture	Smooth		
	Finish	Oil		
	Grades	Plank options: Standard, Exclusive		
	Construction	DuoPlank® LITE Engineered		
DIMENSIONS				
	Thickness	14 mm (9/16")		
	Widths	180 (7")		
	Lengths	1090, 1220, 1470, 1790, 1970, 2100, 2190, 2220, 2400, 2470 mm (3'7", 4', 4'10", 5'11", 6'6", 6'11", 7'2", 7'3", 7'10", 8'1")		
INSTALLATION				
	Plank	Glue down, floating 4-side tongue & groove		
USAGE				
	Recommended usage	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail		
SUBFLOOR HEATING & COOLING				
	Compatibility	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document		
SUSTAINABILITY		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	FSC certified (Mix)		FSC® Certificate-Code: SCS-COC-000609	Meets requirement on request
ENGINEERED WOOD FLOORING STANDARD		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	CE (Conformité Européenne) European standard	EN 14342	CE Compliant	Testing in progress

	NWFA (National Wood Flooring Association) U.S. Standard	ANSI/HPVA EF2009	NWFA Compliant	Testing in progress
LOW EMITTING MATERIALS		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	E1 certificate	EN 717-7	E1 Compliant & E2 Compliant	Testing in progress
	California Air Resources Board (CARB) Certificate for formaldehyde	ASTM E1333	CARB 2 Compliant	Meets requirement
	Émissions dans l'air intérieur A+ label France national Volatile Organic Compound (VOC) A+ label	ISO 16000p 3,6,9	A+ / very low-emission	Testing in progress
	AgBB German label for low emissions	ISO 16000	Meets requirements	Testing in progress
	CA 01350 California Section 01350 Test for VOC Emissions	CA DPHS Standard Practice Section 01350	CA 01350 Compliant	Testing in progress
SLIP RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	CEN/TS 15676 Determination of the anti-skid properties	59 USRV Unpolished Slip Resistance Value	Meets requirement
		DIN 51130	R9 (range 6° - 10°)	Meets requirement
		DIN 51097 / GUV-I 8527	B	Meets requirement
SCRATCH RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
		DIN 68861	4E	Meets requirement
REACTION TO FIRE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	EN14342 Wood flooring + characteristics, evaluation of conformity and marking	EN 13501-1	Cfl-s1	Testing in progress
Installation information		Download the latest version at https://www.hakwood.com/en/downloads/		

Hakwood
Leemansstraat 2
4251 LD Werkendam
the Netherlands
Tel: +31 183 504 266
sales@hakwood.com

Hakwood Inc.
2244 95th St, Suite 200
Naperville IL 60564
United States
Tel: +1 630 219 3388
ussales@hakwood.com

Hakwood