



Cleaning emulsion specially formulated for routine cleaning of wood floor finishes

Hakwood
COMPLETE

CLEAN

Suitable for the routine cleaning of the following surfaces:

- Oil finished hardwood floors
- Lacquer finished hardwood floors

Suitable for the thorough cleaning of the following surfaces:

- Oil finished hardwood floors
- Lacquer finished hardwood floors

Product Properties / Benefits:

Water-based, neutral, all-purpose cleaner for grime on floors.

- Easy application
- Skin friendly (we always recommend the use of protective gloves)
- Also suitable for cleaning stone and vinyl flooring

Technical Data:

Packaging: Plastic bottle
Volume: 0.75 litres/10 litres
Shelf life: Approx. 24 months- protect against frost, always close tightly after use.
Color: Transparent

DILUTION & COVERAGE

Cleaning and coverage is guided by the degree of soiling and desired level of hygiene.

	CLEAN	Water (warm)	Coverage	Frequency
Routine Cleaning	100-200 ml (1 part)	10 L (50-100 parts)	30-100 m ²	Residential use: Weekly as necessary Commercial use: Daily as necessary
Intensive Cleaning	1 L (1 part)	10 L (10 parts)	30-100 m ²	As necessary

DIRECTIONS: Routine Cleaning

1. **Sweep, dust mop** or **vacuum** before cleaning with Hakwood Complete CLEAN.

2. **Shake** the **container** well before use.

3. **Dilute Hakwood Complete CLEAN** at a 1:50-100 ratio, 1 part CLEAN to 50-100 parts warm water.

4. **Apply** a **thin, even coat** in the direction of the wood planks using a microfiber mop or lint-free cloth. The surface to be cleaned should only be damp wiped (not wet). Refresh cleaning liquid with new diluted CLEAN if it becomes dark with dirt.

5. **Clean tools** after use with clean water.

DIRECTIONS: Intensive Cleaning

1. **Sweep, dust mop** or **vacuum** before cleaning with Hakwood Complete CLEAN to remove dirt from the surface.

2. **Shake** the **container** well before use.

3. **Dilute Hakwood Complete CLEAN** at a 1:10 ratio, 1 part CLEAN to 10 parts warm water. Hakwood Complete CLEAN can be used at a higher concentration, up to undiluted, if necessary.

4. Working in sections, **apply** a **thin, even coat** in the direction of the wood planks using a micro-fiber mop or lint-free cloth. The surface to be cleaned should only be damp wiped (not wet).

5. After intensive cleaning, **damp-mop** the **surface** with clean water to remove any residue from the floor.

6. **Clean tools** after use with clean water.

ALL Cleaning:

Recommendation: Rinse mop during cleaning process to avoid leaving a dirty residue behind.

Recommendation: For stubborn spots, sticky spills and shoe marks, use clean cloth or mop pad to apply diluted cleaning agent directly to the soiled area by hand as necessary.

Important Notes:

- On site finished floors, do not use Hakwood Complete CLEAN for a minimum of 24 hours after finish is applied.
- On newly installed, factory finished floors with an oil finish, do not use Hakwood Complete CLEAN for a minimum of 3 weeks.
- Regular maintenance with Hakwood Complete OIL CARE is recommended to replenish the top layer of oil finished flooring which decreases after multiple cleanings.
- Regular maintenance with Hakwood Complete OIL CARE improves the visual appearance and increases the wear-life of the sealed surface.

Protection of the Workplace and the Environment:

Non-flammable. Requires no special protection or precautions in general use. Avoid contact with skin or contact with eyes. Use of barrier cream and ventilation of the work area are recommended.

Hakwood Complete
Leemansstraat 2
4251 LD Werkendam
The Netherlands
info@hakwoodcomplete.com





Provides care, maintenance and prolonged protection for oil finished wood floors

Hakwood
COMPLETE

OIL CARE

Suitable for the routine maintenance of:

- Oil finished hardwood floors

Product Properties / Benefits:

Hakwood OIL CARE has components which produce a refreshing effect to the existing finish. This effect renews lasting care and protection. Dependent on frequency and use, the intervals for thorough cleaning and re-treatment are extended.

- Easy to apply
- Slip-resistant
- Antistatic

Technical Data:

Packaging: Plastic bottle
Volume: 0.75 litres/5 litres
Shelf life: Approx. 24 months- store in original packaging, protect against frost, always close tightly after use.
Color: White
Foot traffic: Immediately after drying

DILUTION & COVERAGE*

OIL CARE maintenance is guided by the degree of use.

	OIL CARE	Water (room temp.)	Coverage	Frequency
Routine Care	200-400 ml	10 L	75-150 m²	Moderate use: every 8-10 weeks Heavy use: every 4 weeks
Intensive Care	500 ml	0	7-10 m²	Every 12 months

* Under normal conditions at 20 °C / 72 °F. Consumption can vary according to the absorbency and condition of the surface of the wood.

DIRECTIONS: Routine Care

1. **Remove** all **dust**, **dirt** and **grease** from the floor using a mop, soft brush or vacuum cleaner before using Hakwood Complete OIL CARE.
2. Bring the container of Hakwood Complete OIL CARE to room temperature and **shake well**.
3. **Dilute Hakwood Complete OIL CARE** at a 1:30 ratio (1 part OIL CARE to 30 parts water).
4. **Using** a suitable **applicator** (microfiber mop or lint-free cloth), apply one damp (not wet) coat over the floor surface in the direction of the planks and allow to dry.
5. **Clean tools** after use with clean water.
6. Floor is **ready** to be walked on **after 60 minutes**.*
* Optimum conditions are 18 – 25 °C, relative humidity < 65 %. Low temperatures and high humidity lengthen, while high temperatures and low humidity shorten the drying time.

DIRECTIONS: Intensive Care

1. **Remove** all **dust**, **dirt** and **grease** from the floor using a mop, soft brush or vacuum cleaner before using Hakwood Complete OIL CARE.
2. Bring the container of Hakwood Complete OIL CARE to room temperature and **shake well**.
3. **Use Hakwood Complete OIL CARE** at a **more intense strength**, 1:10 ratio (1 part OIL CARE to 10 parts water) up to undiluted, to restore finish to scratches and even out floor sheen.
4. **Using a suitable applicator** (microfiber mop or lint-free cloth), apply one damp (not wet) coat over the floor surface in the direction of the planks and allow to dry.
5. **Clean tools** after use with clean water.
6. Floor is **ready** to be walked on **after 60 minutes**.*
* Optimum conditions are 18 – 25 °C, relative humidity < 65 %. Low temperatures and high humidity lengthen, while high temperatures and low humidity shorten the drying time.

Important Notes:
Flecks and applicator marks can be removed with undiluted Hakwood Complete CLEAN on a cloth or non-scratch white pad.

Care tip:
In order to extend the life span of your wood floor, a thorough, periodic cleaning and re-treatment by a professional is essential. The frequency of professional care is dependent on the use and maintenance of the floor. Please refer to your Hakwood Complete professional for more detailed advice.

Protection of the Workplace and the Environment:
Non-flammable. Requires no special protection or precautions in general use. Use of barrier cream and ventilation of the work area are recommended.

Hakwood Complete
Leemansstraat 2
4251 LD Werkendam
The Netherlands
info@hakwoodcomplete.com

