








# DIVINE

LITE COLLECTION

**Hakwood**


## PRODUCT INFORMATION

	<b>Species</b>	European Oak
	<b>Surface texture</b>	Smooth
	<b>Finish</b>	Oil
	<b>Grades</b>	Plank options: Standard, Exclusive
	<b>Construction</b>	DuoPlank® LITE Engineered


## DIMENSIONS

	<b>Thickness</b>	14 mm (9/16")
	<b>Widths</b>	180 (7")
	<b>Lengths</b>	1090, 1220, 1470, 1790, 1970, 2100, 2190, 2220, 2400, 2470 mm (3'7", 4', 4'10", 5'11", 6'6", 6'11", 7'2", 7'3", 7'10", 8'1")


## INSTALLATION

	<b>Plank</b>	Glue down, floating 4-side tongue & groove

## USAGE

	<b>Recommended usage</b>	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail
---	--------------------------	---

## SUBFLOOR HEATING & COOLING

	<b>Compatibility</b>	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document
---	----------------------	--

## SUSTAINABILITY

FSC certified (Mix)

## TEST METHOD

## MINIMUM REQUIREMENT

## PERFORMANCE

FSC® Certificate-Code:  
SCS-COC-000609

Meets requirement  
on request

## ENGINEERED WOOD FLOORING STANDARD

## TEST METHOD

## MINIMUM REQUIREMENT

## PERFORMANCE










**CE (Conformité Européenne)**  
European standard

EN 14342

CE Compliant

Testing in progress

	NWFA (National Wood Flooring Association) U.S. Standard	ANSI/HPVA EF2009	NWFA Compliant	Testing in progress
LOW EMITTING MATERIALS		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	<b>E1 certificate</b>	EN 717-7	E1 Compliant & E2 Compliant	Testing in progress
	<b>California Air Resources Board (CARB)</b> Certificate for formaldehyde	ASTM E1333	CARB 2 Compliant	Meets requirement
	<b>Émissions dans l'air intérieur A+ label</b> France national Volatile Organic Compound (VOC) A+ label	ISO 16000p 3,6,9	A+ / very low-emission	Testing in progress
	<b>AgBB</b> German label for low emissions	ISO 16000	Meets requirements	Testing in progress
	<b>CA 01350</b> California Section 01350 Test for VOC Emissions	CA DPHS Standard Practice Section 01350	CA 01350 Compliant	Testing in progress
SLIP RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	<b>EN14342</b> Wood flooring - characteristics, evaluation of conformity and marking	CEN/TS 15676 Determination of the anti-skid properties	59 USRV Unpolished Slip Resistance Value	Meets requirement
		DIN 51130	R9 (range 6° - 10°)	Meets requirement
		DIN 51097 / GUV-I 8527	B	Meets requirement
SCRATCH RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
		DIN 68861	4E	Meets requirement
REACTION TO FIRE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	<b>EN14342</b> Wood flooring + characteristics, evaluation of conformity and marking	EN 13501-1	Cfl-s1	Testing in progress
<b>Installation information</b>		Download the latest version at <a href="https://www.hakwood.com/en/downloads/">https://www.hakwood.com/en/downloads/</a>		

**Hakwood**  
Leemansstraat 2  
4251 LD Werkendam  
the Netherlands  
Tel: +31 183 504 266  
sales@hakwood.com

**Hakwood Inc.**  
2244 95<sup>th</sup> St, Suite 200  
Naperville IL 60564  
United States  
Tel: +1 630 219 3388  
ussales@hakwood.com

