



Charlotte

Enigma Laminate



Charlotte	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m <sup>2</sup>	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m <sup>3</sup>	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m <sup>2</sup> K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-

Corsa

Enigma Laminate



Corsa	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m <sup>2</sup>	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m <sup>3</sup>	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m <sup>2</sup> K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-



Kelly

Enigma Laminate



Kelly	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m³	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m²K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-



Madison

Enigma Laminate



Madison	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m <sup>2</sup>	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m <sup>3</sup>	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m <sup>2</sup> K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-



Rose

Enigma Laminate



Rose	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m³	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m²K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-

Taylor

Enigma Laminate



Taylor	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m³	-
Classification	Class 23/32	EN-13329
Abrasion resistance	AC4	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	20 year residential	-
Water resistance T joint test	24hr NALFA Fullfilled	NALFA swell test
Technical Specification		
Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m²K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329
Installation		
Installation	Refer to manufacturer guidelines	-
Warranty	20 year residential	-