

Cannes

Movie Laminate



Cannes	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-



Charlie

Movie Laminate



Charlie	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-





Fantasy

Movie Laminate



Fantasy	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-




Festival
Movie Laminate


Festival	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-



Hollywood

Movie Laminate



Hollywood	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-



Musical

Movie Laminate



Musical	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-



Oscar

Movie Laminate



Oscar	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-





Western

Movie Laminate



Western	Description	Test Standard
Country of origin	Poland	-
Dimensions	1380 x 242 x 8mm	EN-13329
Pack size	2.34m ²	-
Pallet quantity	54 packs	-
Weight	16.83kg	-
Construction	HDF 860kg/m ³	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	Aqua pearl	-
Structure	Cyncro 3D	-
Bathroom use	Yes	-
Underfloor heating	Yes	-
Warranty	30 year residential	-
Water resistance T joint test	72hr NALFA Fullfilled	NALFA swell test

Technical Specification

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.066 (m ² K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

Installation

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-

