




Bearfoot

VISTA | ULTRA

Technical Data Information



Product Details	PO NO.:			
	Item Color:	Pyramid		
	Struction;	Multi-layer Engineered Wood Flooring -Herringbone		
	Specification:	18/4*90*450		
	Species:	European Oak	Plywood:	Eucalyptus mixed Poplar
	Grade :	ABCD	Moisture Content (MC):	6-8%
	Bevel:	0.5 for 4 side	Gloss:	About 4 (AS SAMPLE)
	Filler:	Natural filler	Surface finishment	Hand-Brush , Reactive stain , Water-based Lacquer
	Glue Brand	Dynea	Lac Brand:	Loba
	LOC System	Tongue and Groove	Installation:	Floating/Gluedown/Nail down
Maufacturing Process	Selecting veneer and Prepare plywood material →Drying and Balance(40 °C -60 °C)→Pressing→Repair knots→Fixed length and width→Sanding →Hand-Brush →Proflie(Tongue and groove→Reactive stain on surface → Coating→ Packaging			
Technical Date(CE)	Essential Characteristics	Performance	Harmonised Technical Specification	
	Fire Reaction	Dfl-s1	EN 14342: 2013	
	Formaldehyde Emission according to EN 717-1:2005	E1		
	Content of PCP according to CEN/TR 14823:2004	PCP ≤5X10 ⁻⁶ ni		
	Breakcage Resistance	NPD		
	Sliding	NPD		
	Thermal Conductivity	0.13W/mK		
Byological Durability	Class 1			
Certificates	CE,FSC,Floorscore,VOC,CARBIL...			